


自動調心止推滾子軸承


內徑 60 ~ 190 mm



| 主要寸法(mm) |     |     |     | 基本型號         | 基本定格荷重(kgf) |                | 極限速率(rpm) |
|----------|-----|-----|-----|--------------|-------------|----------------|-----------|
| d        | D   | H   | r   |              | C           | C <sub>0</sub> | 油潤滑       |
| 60       | 130 | 42  | 2.5 | <b>29412</b> | 22400       | 41000          | 2000      |
| 65       | 140 | 45  | 3   | <b>29413</b> | 26100       | 49500          | 2400      |
| 70       | 150 | 48  | 3   | <b>29414</b> | 30000       | 58000          | 2200      |
| 75       | 160 | 51  | 3   | <b>29415</b> | 34500       | 60000          | 2100      |
| 80       | 170 | 54  | 3.5 | <b>29416</b> | 35500       | 69000          | 1900      |
| 85       | 150 | 39  | 2.5 | <b>29317</b> | 23100       | 47000          | 2300      |
|          | 180 | 58  | 3.5 | <b>29417</b> | 42000       | 82000          | 1800      |
| 90       | 155 | 39  | 2.5 | <b>29318</b> | 23800       | 49500          | 2300      |
|          | 190 | 60  | 3.5 | <b>29418</b> | 45500       | 89000          | 1700      |
| 100      | 170 | 42  | 2.5 | <b>29320</b> | 26200       | 55500          | 2100      |
|          | 210 | 67  | 4   | <b>29420</b> | 54500       | 100000         | 1500      |
| 110      | 190 | 48  | 3   | <b>29322</b> | 34500       | 75500          | 1800      |
|          | 230 | 23  | 4   | <b>29422</b> | 69000       | 139000         | 1400      |
| 120      | 210 | 54  | 3.5 | <b>29324</b> | 39500       | 85000          | 1000      |
|          | 250 | 78  | 5   | <b>29424</b> | 77000       | 159000         | 1300      |
| 130      | 225 | 58  | 3.5 | <b>29320</b> | 45500       | 98000          | 1500      |
|          | 230 | 85  | 5   | <b>29420</b> | 58500       | 167000         | 1200      |
| 140      | 240 | 60  | 3.5 | <b>29320</b> | 51500       | 114000         | 1400      |
|          | 280 | 85  | 5   | <b>29428</b> | 91500       | 198000         | 1200      |
| 150      | 215 | 39  | 2.5 | <b>29230</b> | 27500       | 67000          | 1800      |
|          | 250 | 60  | 3.5 | <b>29330</b> | 52500       | 119000         | 1400      |
|          | 300 | 90  | 5   | <b>29430</b> | 100000      | 221000         | 1100      |
| 160      | 225 | 39  | 2.5 | <b>29232</b> | 29300       | 74000          | 1700      |
|          | 270 | 67  | 4   | <b>29332</b> | 67000       | 149000         | 1300      |
|          | 320 | 95  | 6   | <b>29432</b> | 115000      | 256000         | 1000      |
| 170      | 240 | 42  | 2.5 | <b>29234</b> | 34000       | 45000          | 1600      |
|          | 280 | 67  | 4   | <b>29334</b> | 67500       | 151000         | 1200      |
|          | 340 | 103 | 6   | <b>29434</b> | 133000      | 300000         | 940       |
| 180      | 250 | 42  | 2.5 | <b>29236</b> | 34500       | 90500          | 1600      |
|          | 300 | 73  | 4   | <b>29336</b> | 79000       | 180000         | 1100      |
|          | 380 | 100 | 6   | <b>29436</b> | 149000      | 345000         | 880       |
| 190      | 270 | 48  | 3   | <b>29238</b> | 47500       | 130000         | 1400      |
|          | 320 | 78  | 5   | <b>29338</b> | 88000       | 203000         | 1100      |
|          | 380 | 115 | 6   | <b>29438</b> | 153000      | 365000         | 940       |

自動調心止推滾子軸承


内径 200 ~ 400 mm



| 主要寸法(mm) |     |     |     | 基本型號         | 基本定格荷重(kgf) |         | 極限速率(rpm) |
|----------|-----|-----|-----|--------------|-------------|---------|-----------|
| d        | D   | H   | r   |              | C           | Co      | 油潤滑       |
| 200      | 340 | 85  | 5   | <b>29340</b> | 108000      | 284000  | 1000      |
|          | 400 | 122 | 6   | <b>29440</b> | 188000      | 470000  | 800       |
| 220      | 360 | 85  | 5   | <b>29344</b> | 110000      | 297000  | 950       |
|          | 420 | 122 | 8   | <b>29444</b> | 193000      | 495000  | 800       |
| 240      | 340 | 60  | 3.5 | <b>29248</b> | 64000       | 189000  | 1200      |
|          | 380 | 85  | 5   | <b>29348</b> | 111000      | 310000  | 900       |
|          | 440 | 122 | 8   | <b>29448</b> | 198000      | 525000  | 750       |
| 260      | 360 | 60  | 3.5 | <b>29252</b> | 70000       | 218000  | 1100      |
|          | 420 | 95  | 6   | <b>29352</b> | 139000      | 385000  | 800       |
|          | 480 | 132 | 8   | <b>29452</b> | 221000      | 590000  | 710       |
| 280      | 380 | 60  | 3.5 | <b>29256</b> | 72500       | 231000  | 1100      |
|          | 440 | 95  | 6   | <b>29356</b> | 142000      | 415000  | 800       |
|          | 520 | 145 | 8   | <b>29456</b> | 278000      | 750000  | 630       |
| 300      | 420 | 73  | 4   | <b>29260</b> | 94500       | 291000  | 950       |
|          | 480 | 109 | 6   | <b>29360</b> | 180000      | 515000  | 710       |
|          | 540 | 145 | 8   | <b>29460</b> | 285000      | 785000  | 600       |
| 320      | 440 | 73  | 4   | <b>29264</b> | 97500       | 310000  | 950       |
|          | 500 | 109 | 6   | <b>29364</b> | 174000      | 515000  | 670       |
|          | 580 | 155 | 10  | <b>29464</b> | 299000      | 840000  | 560       |
| 340      | 460 | 73  | 4   | <b>29268</b> | 100000      | 325000  | 900       |
|          | 540 | 122 | 6   | <b>29368</b> | 216000      | 635000  | 630       |
|          | 620 | 170 | 10  | <b>29468</b> | 360000      | 1000000 | 530       |
| 360      | 500 | 85  | 5   | <b>29272</b> | 125000      | 405000  | 800       |
|          | 560 | 122 | 6   | <b>29372</b> | 219000      | 655000  | 600       |
|          | 640 | 170 | 10  | <b>29472</b> | 370000      | 1050000 | 500       |
| 380      | 520 | 85  | 5   | <b>29276</b> | 127000      | 415000  | 750       |
|          | 600 | 132 | 8   | <b>29376</b> | 269000      | 825000  | 560       |
|          | 670 | 175 | 10  | <b>29476</b> | 395000      | 1120000 | 480       |
| 400      | 540 | 85  | 5   | <b>29280</b> | 129000      | 430000  | 750       |
|          | 620 | 132 | 8   | <b>29380</b> | 265000      | 820000  | 530       |
|          | 710 | 185 | 10  | <b>29480</b> | 440000      | 1270000 | 450       |

自動調心止推滾子軸承

內徑 420 ~ 500 mm



| 主要寸法(mm) |     |     |    | 基本型號    | 基本定格荷重(kgf) |         | 極限速率(rpm) |
|----------|-----|-----|----|---------|-------------|---------|-----------|
| d        | D   | H   | r  |         | C           | Co      | 油潤滑       |
| 420      | 580 | 95  | 6  | 29284   | 165000      | 555000  | 670       |
|          | 650 | 140 | 8  | 29384   | 285000      | 890000  | 500       |
|          | 730 | 185 | 10 | 29484   | 460000      | 1350000 | 430       |
| 440      | 600 | 95  | 6  | 29288   | 167000      | 565000  | 670       |
|          | 680 | 145 | 8  | 29388   | 305000      | 950000  | 480       |
|          | 780 | 206 | 12 | 29488   | 535000      | 1560000 | 400       |
| 460      | 620 | 95  | 6  | 29292   | 168000      | 580000  | 630       |
|          | 710 | 150 | 8  | 29392   | 325000      | 1010000 | 450       |
|          | 800 | 206 | 12 | 29492   | 555000      | 1640000 | 380       |
| 480      | 650 | 103 | 6  | 29296   | 194000      | 680000  | 600       |
|          | 730 | 150 | 8  | 29396   | 340000      | 1080000 | 450       |
|          | 850 | 224 | 12 | 29496   | 590000      | 1780000 | 360       |
| 500      | 670 | 103 | 6  | 292/500 | 196000      | 700000  | 600       |
|          | 750 | 150 | 8  | 293/500 | 355000      | 1160000 | 450       |
|          | 870 | 224 | 12 | 294/500 | 625000      | 1880000 | 340       |

